CHANE PRESSURE ASSIST TOILET 3.8LPF / 1.0GPF

☐ 5722BMY Bowl

☐ **5721BOY** Unlined Pressure Assist Tank

PRODUCT SPECS:

- High efficiency pressure assist toilet

- 3.8Lpf / 1.0Gpf

- Powerful and quiet pressure assisted Sloan FLUSHMATE* Flush assures clean and complete removal of all waste

- Elongated siphon jet action bowl

- Vitreous china

- 17" bowl height

- Chrome tank lever

- Back outlet flange

- 2" Fully glazed ball pass trapway

- Water surface: 11%" x 7%" (295mm x 198mm)

- Toilet seat not included

DIMENSIONS:

447mm W x 755mm D x 800mm H 17½" W x 29¾" D x 31½" H

COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC

- US EPA WaterSense

- ASME A112.19.2 / CSA B45.1

- ANSI A117.1 ADA Guideline

- MaP Premium Tested 1000g

- LEED Compliant

SHIPPING

Bowl:

Cube 5.13 GW 60 lbs

Tank:

Cube 1.43 GW 33 lbs





NOTES: This toilet is designed to rough-in at a minimum dimension of 108 mm (4%'') from finished floorto C/L of outlet. Supply line not included with fixture and must be ordered separately.

Important: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

Products are designed to comply ADA/ANSI A117.1 Standard. It shall be the responsibility of the installer to comply with the local disability codes and standards prior to installing the product.

