

#### **DESCRIPTION**

Vitreous China Floor-Mounted ADA Pressure Assisted Water Closet.

#### **COMPONENTS**

Bowl: Code 2108029Tank: Code 2108016

## **DETAILS**

• Flush Volume: 1.0 gpf (3.8 Lpf)

## **FEATURES**

- White Vitreous China
- Elongated bowl
- Floor mounted, floor outlet
- 12" (305mm) rough-in
- Chrome metal flush handle
- Secure, anti-rocking 3-point tank mounting system
- Powered by Flushmate® brand pressure assisted flushing technology to achieve 1,000g MaP score
- Over 60 ft (18.3 m) drainline carry performance
- Water spot area: 11 1/4 x 93/4 (286 mm x 248 mm)
- Smooth, quiet cable activated flush handle left hand
- Fully glazed trapway
- Closet bolts and caps included
- Toilet seat and wax ring not included

## **PLUMBING SYSTEM REQUIREMENTS**

Maximum Static Pressure: 80 PSI (552 kPa)
Minimum Static Pressure: 25 PSI (172 kPa)

## DOWNLOADS

- Pressure-Assisted Installation Instructions
- Flushmate Owner's Manual
- Pressure-Assisted Repair and Maintenance Guide
- Additional Downloads



## **COMPLIANCES & CERTIFICATIONS**













(cUPC Green Certified, ADA Compliant, WaterSense Listed, CalGreen Compliant, CEC Compliant, NOM Certified)

#### **NOTES**

All vitreous china dimensions shown in these drawings are nominal and not to scale. Dimensions can vary within the tolerances established in the governing ASME A112.19.2/CSA B45.1 standard. It is important to consider this when planning rough-in and plumbing layouts.

All information contained within this document subject to change without notice.



# **ROUGH-IN**

